

RING COTTERS

MB Spring Wire, Zinc Coated or Type 302 Stainless Steel

PART NO.	O.D. X WIRE DIAM	USE ON DIAMETER	WT. PER 1000
3703	5/8 X .048	3/16 - 1/4	1.4
3705	3/4 X .048	1/4 - 5/16	1.6
3707	1 X .062	3/8 - 7/16	4
3709	1-1/8 X .072	7/16 - 1/2	5.8



*SS Suffix indicates 302 stainless steel
Less 5% on 50,000 pieces or more

KEY RINGS

SPRING STEEL, AVAILABLE NICKEL & ZINC COATED

PART NUMBER	INSIDE DIAMETER	THICKNESS		WT PER 1000
		A	B	
KR 1	.335	.056	.083	1.1
KR 3	.425	.063	.093	1.7
KR 5	.550	.077	.103	3.5
KR 7	.719	.092	.120	5.1
KR 8	.833	.080	.127	6.6
KR 9	.920	.092	.120	7.6
KR 10	1.11	.088	.139	10.6
KR 11	1.188	.109	.156	14.6
KR 12	1.315	.098	.172	16.1



Brass & Stainless Quoted on Request

RING CLIPS - ZINC COATED

PART NUMBER	FITS SHAFT SIZE	SHAFT CLEARANCE	WIRE DIA.	OVERALL LENGTH	WT PER M
RC-8	1/4 HEAVY	.267/.257	.041	.844	1.1
RC-9H	1/4 EXTRA HEAVY	.270/.260	.054	.936	1.8
RC-10	5/16 REGULAR	.330/.320	.047	1.044	1.8
RC-14	3/8 REGULAR	.392/.382	.054	1.214	2.3
RC-22	1/2 REGULAR	.520/.510	.062	1.420	4.1
RC-24	1/2 HEAVY	.520/.510	.072	1.456	6.8
RC-30	5/8 REGULAR	.645/.635	.072	1.690	7.9
RC-34	3/4 REGULAR	.770/.760	.080	2.081	10.0
RC-36	3/4 HEAVY	.770/.760	.091	2.166	13.0
RC-40	7/8 HEAVY	.895/.885	.105	2.506	20.6
RC-42	1 REGULAR	1.020/1.010	.105	2.756	22.8



Stainless Quoted on Request