

SAFETY PIN FASTENERS ZINC COATED

SPRING WIRE



STANDARD DUTY / without coil

WW NO.	WIRE DIA.	INSIDE DIMENSION	WT. PER 1000
501	.047	1-1/4	2-1/4
502	.047	1-1/2	2-1/2
506	.062	2-1/2	6
507	.047	2-3/16	3-3/8

COILED

WW NO.	INSIDE CLEARANCE	WIRE DIA.	WT. PER 1000
505	2-1/4 X 5	.243	370
504	1-5/8 X 5	.243	330
503	1-1/2 X 3	.177	150
508	1-1/8 X 3-3/4	.148	87
509	7/8 X 2-3/4	.125	44
510	3/8 X 15/16	.048	2.25
511	3/8 X 1-1/16	.062	4.4
512	5/8 X 1-11/16	.091	22
513	3-1/4 X 7-1/2	.312	900




AA55488 SAFETY PINS

PART #	WIRE DIA.	INSIDE DIMENSION	WT. PER 1000
AA554881	.051	7/8 x 5/32	2.2
AA554882	.041	9/16 x 5/32	1.1

Type 316 Stainless Steel

A-A-55487- LOCK PINS

FORMERLY AN415- LOCK PINS



PART NUMBER	WIRE DIAM.	WT PER 1000
A-A-55487-2	0.0800	6
A-A-55487-3	0.0295	0.25
A-A-55487-4	0.0585	1.9
A-A-55487-5	0.0720	4.5
A-A-55487-6	0.0915	8.5

A-A-55487-1- LOCK PINS

FORMERLY AN415-1- LOCK PINS



PART NUMBER	WIRE DIAM.	WT PER 1000
A-A-55487-1-1	0.080	5
A-A-55487-1-2	0.080	6
A-A-55487-1-3	0.080	7.5
A-A-55487-1-4	0.080	9
A-A-55487-1-5	0.080	10.5
A-A-55487-1-6	0.080	12
A-A-55487-1-7	0.080	13.5

Note: Second dash indicates length in inches.

Type 316 Stainless Steel in
accordance with ASTM A313